


# Meeting the Geodetic Challenge of the NRC's Decadal Survey



John LaBrecque  
Lead, Earth Surface and Interior Focus Area  
NASA Earth Science Division  
Washington, DC 20546


# Earth Surface and Interior Focus Area Strategic Plan: Living on a Restless Planet <http://solidearth.jpl.nasa.gov>

## ESI Strategic Goals-




1. What is the nature of deformation at plate boundaries and what are the implications for earthquake hazards?
2. How do tectonics and climate interact to shape the Earth's surface and create natural hazards?
3. What are the interactions among ice masses, oceans, and the solid Earth and their implications for sea level change?
4. How do magmatic systems evolve and under what conditions do volcanoes erupt?
5. What are the dynamics of the mantle and crust and how does the Earth's surface respond?
6. What are the dynamics of the Earth's magnetic field and its interactions with the Earth system?

## ESI Achievements



GRACE: 1st Time Variable Gravity & Mass Flux

Earthquake Forecasting  
13 of 14 Earthquakes



SRTM  
1st Uniform Global Topography




## ESI Component Programs

**Natural Hazards**  
Predictive Models  
Remote Sensing  
Natural Laboratories


**Space Geodesy**  
Celestial Ref Frame  
Terrestrial Ref Frame  
Earth Rotation  
Crustal Dynamics

**Planetary Interior**  
Geomagnetic Models  
Gravity Models  
Geodynamic Models


## ESI Strategic Mission Priorities



1. Develop Geodetic Imaging Approach: DESDynI, International Partners



2. Renew Global Geodetic Network Approach: GGOS Partnerships



3. Expand Geopotential Field Exploration Approach: GRACE-FO, International Partnerships, Technology Development, GRACE-II

# Presidents FY011 Budget Enables Next-Generation Space Geodetic Development

## • Development Studies

- Six US Agencies (NASA NGA, NOAA, NSF, USNO, and USGS) supporting the US National Research Council study National Requirements for Precision Geodetic Infrastructure.
- NASA supports a Geodetic Study Group to develop the requirements for the next Generation Geodetic Network
  - Encouraged development of GGOS Standard based upon Sea level Change requirements. (1.0 mm accuracy, 0.1 mm/yr stability)
  - Funding Development of Network Performance Simulations
  - SLR Retro-reflector Standard
  - Placement of Retro-reflectors on the GPS III Satellites
  - Supporting Network and Communications Bureau of the GGOS
  - Supporting Central Bureaus of the IGS, IVS, ILRS




## • Instrument Development

- Prototype development of Next Gen Geodetic Observatory
- NGSLR, VLB2010, TRIG GNSS Science Receiver
- *In situ* Continuous Co-location and Bias monitoring
- Development of Decadal Study Missions:
- SMAP, ICESAT-2, DESDynI Radar and Lidar, GRACE-FO, CLARREO

## • Development of Decadal Study Missions


- SMAP, ICESAT-2, DESDynI Radar and Lidar, GRACE-FO, CLARREO

# Scientific and Societal Requirements for GNSS based Space Geodesy are Growing



Climate Change Research




Geohazards Research and Mitigation



Navigation

Positioning


Time Transfer



# The Geodetic Challenge of the National Research Council's Decadal Study

## \$2.4 B in Space Missions that depend upon capable Geodetic Science, Geodetic Technology, and Geodetic Infrastructure.

Decadal Survey Mission	Mission Description	Orbit	Instruments	Rough Cost Estimate
<b>Timeframe 2010 – 2013, Missions listed by cost</b>				
CLARREO (NASA portion)	Solar radiation, spectrally resolved forcing and response of the climate system	LEO, Precessing	Absolute, spectrally-resolved interferometer	\$200 M
SMAP	Soil moisture and freeze/thaw for weather and water cycle processes	LEO, SSO	L-band radar L-band radiometer	\$300 M
ICESat-II	Ice sheet height changes for climate change diagnosis	LEO, Non-SSO	Laser altimeter	\$300 M
DESDynI	Surface and ice sheet deformation for understanding natural hazards and climate; vegetation structure for ecosystem health	LEO, SSO	L-band InSAR Laser altimeter	\$700 M
<b>Timeframe: 2013 – 2016, Missions listed by cost</b>				
HypIRI	Land surface composition for agriculture and mineral characterization; vegetation types for ecosystem health	LEO, SSO	Hyperspectral spectrometer	\$300 M
ASCENDS	Day/night, all-latitude, all-season CO <sub>2</sub> column integrals for climate emissions	LEO, SSO	Multifrequency laser	\$400 M
SWOT	Ocean, lake, and river water levels for ocean and inland water dynamics	LEO, SSO	Ka-band wide swath radar C-band radar	\$450 M
GEO-CAPE	Atmospheric gas columns for air quality forecasts; ocean color for coastal ecosystem health and climate emissions	GEO	High and low spatial resolution hyperspectral imagers	\$550 M
ACE	Aerosol and cloud profiles for climate and water cycle; ocean color for open ocean biogeochemistry	LEO, SSO	Backscatter lidar Multiangle polarimeter Doppler radar	\$800 M
<b>Timeframe: 2016 -2020, Missions listed by cost</b>				
LIST	Land surface topography for landslide hazards and water runoff	LEO, SSO	Laser altimeter	\$300 M
PATH	High frequency, all-weather temperature and humidity soundings for weather forecasting and SST <sup>a</sup>	GEO	MW array spectrometer	\$450 M
GRACE-II	High temporal resolution gravity fields for tracking large-scale water movement	LEO, SSO	Microwave or laser ranging system	\$450 M
SCLP	Snow accumulation for fresh water availability	LEO, SSO	Ku and X-band radars K and Ka-band radiometers	\$500 M
GACM	Ozone and related gases for intercontinental air quality and stratospheric ozone layer prediction	LEO, SSO	UV spectrometer IR spectrometer Microwave limb sounder	\$600 M
3D-Winds (Demo)	Tropospheric winds for weather forecasting and pollution transport	LEO, SSO	Doppler lidar	\$650 M



ISBN: 0-309-66714-3, 456 pages, 8 1/2 x 11, (2007)

Download Free from:

<http://www.nap.edu/catalog/11820.html>

**The Requirement for Precise Measurement and Maintenance of the Terrestrial Reference Frame: (*Earth Science and Applications from Space: National Imperatives for the Next Decade and Beyond, NRC,2007*)**

According to the NRC Decadal Survey:

“The geodetic infrastructure needed to enhance, or even to maintain the terrestrial reference frame is in danger of collapse (cf. Chapter 1). Improvements in both accuracy and economic efficiency are needed. Investing resources to assure the improvement and the continued operation of this geodetic infrastructure is a requirement of virtually all the missions for every Panel in this study.


The terrestrial reference frame is realized through integration of the high precision networks of the Global Positioning System (GPS), Very Long Baseline Interferometry (VLBI), and Satellite Laser Ranging (SLR). It provides the foundation for virtually all space-based and ground-based observations in Earth science and global change, including remote monitoring of sea level, sea surface topography, plate motions, crustal deformation, the geoid, and time-varying gravity from space. It is through this reference frame that all measurements can be inter-related for robust, long-term monitoring of global change. A precise reference frame is also essential to interplanetary navigation and diverse national strategic needs.”

**The Requirement for Precise Measurement and Maintenance of the Terrestrial Reference Frame: (*Earth Science and Applications from Space: National Imperatives for the Next Decade and Beyond, NRC,2007*)**

“The geodetic infrastructure needed to enhance, or even to maintain the terrestrial reference frame is in danger of collapse (cf. Chapter 1). Improvements in both accuracy and economic efficiency are needed. Investing resources to assure the improvement and the continued operation of this geodetic infrastructure is a requirement of virtually all the missions for every Panel in this study.


The terrestrial reference frame is realized through integration of the high precision networks of the Global Positioning System (GPS), Very Long Baseline Interferometry (VLBI), and Satellite Laser Ranging (SLR). It provides the foundation for virtually all space-based and ground-based observations in Earth science and global change, including remote monitoring of sea level, sea surface topography, plate motions, crustal deformation, the geoid, and time-varying gravity from space. It is through this reference frame that all measurements can be inter-related for robust, long-term monitoring of global change. A precise reference frame is also essential to interplanetary navigation and diverse national strategic needs.”

Positioning Precision



Applied Geodesy

Precision Geodesy



# Strengthened GNSS- Global Geodetic Observing System Collaboration will improve GNSS performance and Scientific Productivity

International Terrestrial Reference Frame (ITRF)

International Earth Rotation Service  
(IERS)

Precision GPS Orbits and Clocks, Earth Rotation Parameters, Station Positions


Very Long Baseline  
Interferometry  
(IVS)




Satellite Laser  
Ranging  
(ILRS)






Global Navigation  
Satellite Systems  
(IGS)



Doppler Orbit Determination  
and Radiopositioning  
Integrated on Satellite  
(IDS)



# Improving the performance of the Global Geodetic Observing System is critical to understanding the future impact of Sea level Change



The GGOS Geodetic Reference Frame Requirement for Sea Level Measurement

**1 mm reference frame accuracy and 0.1 mm/yr stability**

# GNSS Challenge: 60 to 90 High Precision Radio Sources Within the Decade (+ QZSS & GAGAN)

- Will the Signals be interoperable?
- Will the Scientific Geodetic Community have access to the precise signals?
- Will real time access to the relevant codes be available for scientific geodesy?
- Will the GGOS provide Precision Tracking via GNSS, SLR, and VLBI Networks?


GPS




Galileo



GLONASS




Beidou



# Achieving ITRF Requirements Through Satellite Laser Ranging

## SLR Enables:

- Comparison of collocated radiometric and optical measurements used for model improvements
- Isolation of systematic errors in GNSS constellations and improves the reference frame accuracy
  - Variation of range and phase centers important for space users because they sample the signals far off the transmit boresight
- Improved models and reference frames necessary to support civilian and scientific requirements for higher PNT accuracy
  - Global sea height change measurement from space requires 1 mm/year precision, so reference frame needs to be constant to 0.1 mm/yr



# ILRS Retro-reflector Standard for GNSS Satellites

- Retro-reflector payloads for the GNSS satellites GPS, GLONASS, and COMPASS should have an “effective cross-section” of 100 million sq. meters (5 times that of GPS-35 and -36) for GNSS satellite; GLONASS is first to comply.
- The parameters necessary for the precise definition of the vectors between the effective reflection plane, the radiometric antenna phase center and the center of mass of the spacecraft be specified and maintained with an accuracy of a mm;
- Further Recommendation: Retro-reflector payloads for satellites such as Galileo in higher orbits should scale the “effective cross-section” to compensate for the  $R^{**4}$  reduction in signal strength;



GPS 35/36



ETS VIII

# A 16 Station SLR Network Tracking a GNSS constellation could provide 4mm/yr origin and .02mm/yr scale accuracy (results/sqrt 52, Pavlis et al, 2010)

## Error in ITRF Origin [mm]

Days Tracked	1 SVN	2 SVN	3 SVN	4 SVN	5 SVN	6 SVN
1	395.9	561.3	263.0	136.7	107.6	70.3
2	399.0	56.9	50.9	43.3	44.1	61.5
3	745.6	93.0	99.3	43.8	38.0	43.2
4	486.7	49.4	78.8	50.2	44.8	68.9
5	436.5	77.6	54.9	48.0	43.8	31.0
6	475.7	78.4	55.7	51.2	47.2	30.6
7	276.0	97.0	54.7	49.0	44.7	28.4

## Error in ITRF Scale [mm]

Days Tracked	1 SVN	2 SVN	3 SVN	4 SVN	5 SVN	6 SVN
1	782.4	30.0	10.6	9.1	6.0	3.7
2	329.6	21.8	8.7	8.1	6.3	3.5
3	362.4	25.9	8.1	2.9	1.3	2.7
4	315.1	12.3	6.1	2.8	1.8	1.9
5	199.9	10.6	3.8	3.0	1.8	1.1
6	190.5	7.2	5.2	3.3	1.3	1.3
7	99.8	8.5	4.9	3.1	2.6	0.6




JCET

CSR

# Network Size



## Network size vs. "x" Parameter Accuracy



"x":  
Origin,  
Scale,  
EOP,  
their  
rates,  
etc.



GGOS Networks, Communications and Infrastructure IWG Meeting,  
Perugia, Italy, 9 July, 2007



# NASA is Building the Next Generation Geodetic Observatory at GGAO



VLBI



Continuous monitoring of  
Instrument co-location



SLR



DORIS

Real Time  
Communications Network  
For  
Data Analysis  
Network Control



GNSS



# NASA's Climate Initiative Supports the Development of an Improved Observing System Earth System Mass Transport

## Rebuild the Satellite Observing System

## Rebuild the Global Geodetic Observing Network

Decadal Survey Mission	Mission Description	Orbit	Instruments	Rough Cost Estimate
<b>Timeframe 2010 – 2013, Missions listed by cost</b>				
CLARREO (NASA portion)	Solar radiation, spectrally resolved forcing and response of the climate system	LEO, Precessing	Absolute, spectrally-resolved interferometer	\$200 M
SMAP	Soil moisture and freeze/thaw for weather and water cycle processes	LEO, SSO	L-band radar L-band radiometer	\$300 M
ICESat-II	Ice sheet height changes for climate change diagnosis	LEO, Non-SSO	Laser altimeter	\$300 M
DESDynI	Surface and ice sheet deformation for understanding natural hazards and climate; vegetation structure for ecosystem health	LEO, SSO	L-band InSAR Laser altimeter	\$700 M
<b>Timeframe: 2013 – 2016, Missions listed by cost</b>				
HypIRI	Land surface composition for agriculture and mineral characterization; vegetation types for ecosystem health	LEO, SSO	Hyperspectral spectrometer	\$300 M
ASCENDS	Day/night, all-latitude, all-season CO <sub>2</sub> column integrals for climate emissions	LEO, SSO	Multifrequency laser	\$400 M
SWOT	Ocean, lake, and river water levels for ocean and inland water dynamics	LEO, SSO	Ka-band wide swath radar C-band radar	\$450 M
GEO-CAPE	Atmospheric gas columns for air quality forecasts; ocean color for coastal ecosystem health and climate emissions	GEO	High and low spatial resolution hyperspectral imagers	\$550 M
ACE	Aerosol and cloud profiles for climate and water cycle; ocean color for open ocean biogeochemistry	LEO, SSO	Backscatter lidar Multiangle polarimeter Doppler radar	\$800 M
<b>Timeframe: 2016 -2020, Missions listed by cost</b>				
LIST	Land surface topography for landslide hazards and water runoff	LEO, SSO	Laser altimeter	\$300 M
PATH	High frequency, all-weather temperature and humidity soundings for weather forecasting and SST <sup>d</sup>	GEO	MW array spectrometer	\$450 M
GRACE-II	High temporal resolution gravity fields for tracking large-scale water movement	LEO, SSO	Microwave or laser ranging system	\$450 M
SCLP	Snow accumulation for fresh water availability	LEO, SSO	Ku and X-band radars K and Ka-band radiometers	\$500 M
GACM	Ozone and related gases for intercontinental air quality and stratospheric ozone layer prediction	LEO, SSO	UV spectrometer IR spectrometer Microwave limb sounder	\$600 M
3D-Winds (Demo)	Tropospheric winds for weather forecasting and pollution transport	LEO, SSO	Doppler lidar	\$650 M




NRC Geodetic Science Missions



# First UAVSAR Measurement of an Earthquake

<http://uavsar.jpl.nasa.gov>


- **Response:** Displacement and disturbance maps
- **Forecasting:** Strain migration  
⇒ Future earthquakes



# DESDynI is a Dual Spacecraft Mission 2017 Launch


## D-SAR

L-Band Sweep SAR Quad-Pol.  
700 km Orbit-  
Dawn-Dusk Orbit  
3 year lifetime  
270 km Swath -13 day repeat




## D-Lidar

1 m telescope (~393 km orbit)  
Fixed, nadir orientation  
5 Beams (35% duty cycle)  
2 year lifetime  
Dawn-Dusk Orbit  
91 day Repeat




# DESDynI Lidar tracks over GRACE mass anomalies (*Luthcke et al.*)

420 nm radius DESDynI Lidar Donut hole  
coverage  
86.4 % Antarctic 99% of Greenland



# DESDynI-Lidar simulated Recovery of Jakobshavn Isbrae Topographic Change




**1- $\sigma$  Error in Recovered Signal (ABS(truth-estimated))**

Mission Configuration and data used	Spatial Resolution (km X km)	3 Year Trends (cm/yr)	1 Year Trends (cm/yr)	6 month change (cm)	No. of Obs.	Post-fit Obs. Residual (m)
1. 50% random pass loss from clouds unless otherwise noted.	25	1.0	7.2	7.5	12658	1.33
2. 30 m along-track sampling unless otherwise noted.	10	1.1	11.29	19.9	2850	1.52
DESDynI 5-year mission	5	4.3	19.4	25.7	719	1.48
	2.5	4.4			179	1.44


GRACE-Follow-ON:


Launch Date 2016

GRACE clone with laser ranging system




# Space Geodesy is a Science that Cuts a Wide and Important Swath through the Scientific Landscape





# Next Generation Constellations of GNSS Remote Sensing Satellites will Provide Tomographic Measurements of the Ionosphere, Atmosphere and Characterize the Earth's Surface Using

## REFRACTION



## REFLECTION





# Will the NRC missions of GRACE FO + DESDynI + SMAP+Geodetic Networks Provide High Resolution Separable Measurements of Hydrology and Tectonics?

